

XRVAP PRO

PROFESSIONAL LINE XRVAP PRO



Steam cleaner - 10 bar with continuous flow and digital display.

Technical features	Data
Colour:	Black/transparent blue/woodline/chrome
Steam production:	continuous flow with automatic filling system
Boiler Steam temperature:	180 ° C
Heating time:	4 minutes
Pressure (bar):	10
Boiler Power Consumption (W):	3200
Boiler volume (l):	2
Steam EV1 (gr/min):	76 gr/min
Steam EV2 (gr/min):	84 gr/min
Steam EV1+EV2 (gr/min):	102 gr/min
Boiler material:	stainless steel AISI 304
Steam regulation on steam hose:	activation on the pistol grip with indication in digital display frontal panel
Total Power Consumption (W):	3200
Iron Power Consumption (W):	800
Voltage:	230 V AC / 50 Hz
Tank capacity (l):	1,3
Water level alarm:	visual (digital display) and acoustic
Pressure indicator:	visual (digital display)
Water pump power:	48W 220-240V AC/50Hz
Low tension voltage on handgrip:	9V DC
Power cable:	7 m
Net weight (only machine) (kg):	7,80
Machine Dimensions (DxH):	450x390 mm
Certification Reached:	CE



XRVAP PRO

PROFESSIONAL LINE
3000/3000D Medical



Steam cleaner with continuous flow, vacuum function (water filter) available with detergent function. This model has reached an important certification: CE Medical which gives to the machine an additional value and the possibility to be used in hospitals. The trolley (optional) is light and versatile.

Technical features	Data
Colour:	White
Steam production:	continuous flow with automatic filling system
Boiler Steam temperature:	161 °C
Heating time:	5 minutes
Pressure (bar):	6,5
Boiler Power Consumption (W):	2200
Boiler volume (l):	2
Steam EV1 (gr/min)	48 gr/min
Steam EV2 (gr/min):	56 gr/min
Steam EV1+EV2 (gr/min):	64 gr/min
Detergent injection quantity:	10 cc/min
Boiler material:	Stainless Steel AISI 304
Vac Motor suction power (Kpa):	19
Vac Motor Power Consumption (W):	1000
Total Power Consumption (W)	3200
Voltage:	230 V AC / 50 Hz
Tank capacity (l):	2,2
Waste tank capacity (l)	1
Water level alarm:	visual and acoustic
Pressure indicator:	visual
Detergent Tank capacity (l):	1l
Detergent tank - level alarm:	visual and acoustic
Steam activation:	activation on the pistol grip - with indication in led frontal panel
Vacuum activation:	activation on the pistol grip - with indication in led frontal panel
Detergent activation:	activation on the pistol grip - with indication in led frontal panel
Water pump power:	48W 220-240V AC / 50Hz
Low tension voltage on handgrip:	9 V
Power cable:	7 mt
Detergent pump power:	21W 220-240V AC / 50Hz
Net weight (only machine) (kg):	14,5
Dimensions (LxWXH):	530x400xH.400
Certification Reached:	CE MEDICAL

XRVAP PRO

PROFESSIONAL LINE Inox 6000



Stainless steel steam cleaner with continuous flow - 10 bar, vacuum function (water filter), detergent or hot water injection.

Technical features	Data
Colour:	steel grey
Steam production:	continuous flow with automatic filling system
Boiler Steam temperature:	180°C
Heating time:	4 minutes
Pressure (bar):	10
Boiler Power Consumption (W):	3200
Boiler volume (l):	2
Steam EV1 (gr/min):	73 gr/min
Steam EV2 (gr/min):	84 gr/min
Steam EV1+EV2 (gr/min):	100 gr/min
Detergent injection quantity:	10 cc/min
Boiler material:	Stainless steel AISI 304
Steam regulation on steam hose:	activation on the pistol grip-with indication in digital display on frontal panel
Vac Motor suction power (Kpa):	21,5
Vac Motor Power Consumption (W):	1200
Total Power Consumption (W):	3400
Voltage: 2	30 V AC / 50 Hz
Tank capacity (l):	5
Waste tank capacity (l) :	6,5
Water level alarm:	visual and acoustic
Pressure indicator:	visual
Detergent Tank capacity (l):	5 L
Detergent tank - level alarm:	visual and acoustic
Hot Water Injection + Steam (gr/min):	364 gr/min.
Water pump power:	48W 220-240V AC/50Hz
Low tension voltage on handgrip:	9 V DC
Power cable:	7 m
Net weight (only machine) (kg):	35
Dimensions (LxWXH):	440x465x705 mm
Certification Reached:	CE

XRVAP PRO

PROFESSIONAL LINE
INOX 8000



Professional stainless steel steam cleaner (10bar) with automatic refili, hot water jet and detergent function .

Technical features	Data
Colour:	Stainless steel grey
Steam production:	Continuous flow with automatic filler system
Boiler Steam temperature:	180 °C
Heating time:	4 minutes
Pressure (bar):	10
Boiler Power Consumption (W):	3200
Boiler volume (l):	2
Steam EV1 (gr/min)	73 gr/min
Steam EV2 (gr/min):	84 gr/min
Steam EV1+EV2 (gr/min):	100 gr/min
Detergent injection quantity:	10 cc / min
Boiler material:	Stainless steel 304
Steam regulation on steam hose:	Activation on the handle τ with printed board indications. Lights upon the front panel
Total Power Consumption (W):	3200
Voltage:	230 V AC / 50 Hz
Tank capacity (l):	5
Water level alarm:	Visual and acoustic
Pressure indicator:	Visual
Detergent Tank capacity (l):	3 l
Detergent tank - level alarm:	Visual and acoustic
Hot Water Injection + Steam (gr/min):	364 gr/min
Water pump power:	48W 220 - 240V AC / 50Hz
Low tension voltage on handgrip:	9V DC
Power cable:	7 mt
Net weight (only machine) (kg):	17
Dimensions (LxWXH)	320x400x320 mm
Certification Reached:	CE

XRVAP PRO

PROFESSIONAL LINE Odonto-Steam



Stainless steel steam cleaner with continuous flow suitable for dentist labs and jewelry

Technical features	Data
Colour:	stainless steel
Steam production:	continuous flow
Boiler Steam temperature:	171°C
Heating time:	5 minutes
Pressure (bar):	10 bar
Boiler Power Consumption (W):	3200
Boiler volume (l):	2
Steam EV1 (gr/min):	36 gr/min minimum regulation - 76 gr/min maximum regulation
Boiler material:	Stainless Steel AISI 304
Steam regulation on steam hose :	no
Total Power Consumption (W):	3200
Voltage:	230 V 50 Hz
Tank capacity (l):	5
Water level alarm:	visual and acoustic
Pressure indicator:	visual
Hot Water Injection + Steam (gr/min):	173 gr/min minimum regulation - 224 gr/min maximum regulation
Water pump power:	48W
Low tension voltage on handgrip:	9 V
Power cable:	7 m
Net weight (only machine) (kg):	8,8
Dimensions (LxWXH):	322x365x330 mm
Certification Reached:	CE